

LED Linear Strip

3-Wattages + 3-CCT (35/40/50K), Damp Rated, Up to 135 lm/W, Dimmable + Smart

4-FT Low Bay, and 8-FT High Bay Models

FEATURES	
Lumen Output	3120 to 12150 lumens
Efficacy	Up to 135 lm/W
Input Voltage	120-277V
Dimmable	0-10V Continuous
Size	4-FT, 8-FT
CCT	Select (3500K, 4000K, 5000K)
Rating	Damp Location
Warranty	5 Years

APPLICATIONS

Premium indoor luminaire for hanging or surface mounting in ceiling spaces less than 25 feet. Suitable for gymnasiums, warehouses, manufacturing, packaging, storage, aisles, work-stations, and covered decks.

CONSTRUCTION

Manufactured for durability using aluminum sheet housing with semi-gloss coating to resist corrosion, discoloration, and scratching. Damp Location rated.

ELECTRICAL

Input voltages 120-277V models with 0-10V Continuous Dimming. Tunable 3-CCT (3500K, 4000K, 5000K) and Tunable 3-Wattages. Operating temperatures -4°F to 104°F (-20°C to 40°C).

MOUNTING

Surface mounting standard. Optional 10-FT Aircraft Cables for hanging available.

OPTICS

Anti-UV Frosted Polycarbonate Lens standard.

CONTROLS

Installed fixture mounted Microwave Sensor available. Remote Control available.

EMERGENCY


Installed 90 Minute Emergency Backup Battery LED Driver options available.

LISTINGS

DLC Premium listed. UL certified to meet US and Canadian standards. FCC and RoHS compliant.

WARRANTY

5 year exclusive limited warranty.



Remote Controller

- LCD screen display
- Memory and apply function
- Universal smart controller for dimmable sensor



Junction Box Cover Plate

- To cover the ceiling hole
- Color: White electrical box cover



Linkable Connector

- For continuous row installation
- Color: White steel



Suspension Kit




- For suspend the strip light
- Material: stainless steel

TUNABLE CORRELATED COLOR TEMPERATURES (CCT)

3500K

4000K

5000K



SPECIFICATIONS

ENERGY DATA

Input Voltage: 120-277V
Input Frequency: 50/60 Hz
Wattage: 3-Wattages (40W Max, 90W Max)
Power Factor: >0.9
Total Harmonic Distortion (THD): <10%
Operating Temperature: -4°F to 104°F (-20°C to 40°C)

LIGHTING DATA

Lumens: 3120 to 12150
Lumens Per Watt: Up to 135 lm/W
Correlated Color Temperature (CCT): 3-CCT (35K, 40K, 50K)
Dimmable: 0-10V
Color Rendering Index (CRI): >80
L70: 50000 hours

ORDERING INFORMATION

Model	Size	Wattage	Voltage	Current	Lumens	Efficacy	CCT	Dimming	Color	Dimensions
LS01-4FT-40/32/24W-3CCT	4-FT	(24W, 32W, 40W)	120-277V	0.22A@120V, 0.10A@277V 0.29A@120V, 0.13A@277V 0.37A@120V, 0.16A@277V	3120 4160 5200	130 lm/W	(3500K, 4000K, 5000K)	0-10V	White	48.0"L x 2.9"W x 3.27"H
LS01-8FT-90/75/64W-3CCT	8-FT	(64W, 75W, 90W)	120-277V	0.59A@120V, 0.26A@277V 0.69A@120V, 0.30A@277V 0.83A@120V, 0.36A@277V	8640 10125 12150	135 lm/W	(3500K, 4000K, 5000K)	0-10V	White	92.7"L x 2.9"W x 3.27"H

Housing	Mount	Control	Emergency
	LCKIT	Linkable Connector (Fits: Strip Lights)	Sensor 12V DC Integrated MW Bi-Level,Auto Jack Connection, 0-10V dimming,Daynight Harvest Remote Controller Smart Controller For Dimmable Sensor
	ACKIT	Pair of 10-FT Aircraft Hanging Cables (Fits: Strip Lights)	
	JBKIT	Junction Box Cover Plate	
			EM8 (BLD-CM08H-YYY-8W) INSTALLED - Emergency LED Driver, 8W, 90-Minute Battery

PHYSICAL DIMENSIONS

4-FT Models

48.0"L x 2.9"W x 3.27"H

8-FT Models

92.7"L x 2.9"W x 3.27"H

