

# LED Canopy Light

3-Wattages + 3-CCT (35/40/50K), Wet Rated, 130 lm/W, Dimmable + Smart

FEATURES	
Lumen Output	5200 to 1300 lumens
Efficacy	130 lm/W
Input Voltage	120-277V
Dimmable	0-10V Continuous
CCT	Select (3500K, 4000K, 5000K)
Rating	Wet Location
Warranty	5 Years

**APPLICATIONS**  
Premium outdoor luminaire for surface mounting in ceiling spaces less than 25 feet. Suitable for general storage, cold storage, parking garages, and canopies.

**CONSTRUCTION**  
Manufactured for weather-proof durability using solid heavy duty die cast aluminum housing with anti-UV polyester coating to resist water, salt, corrosion, discoloration, and scratching. Wet Location rated.

**ELECTRICAL**  
Input voltages 120-277V with 0-10V Continuous Dimming. Tunable 3-CCT (3500K, 4000K, 5000K) and Tunable 3-Wattage. Operating temperatures -40°F to 104°F (-40°C to 40°C).

**MOUNTING**  
Surface mounted installation.

**OPTICS**  
Anti-UV Frosted Prismatic Polycarbonate Lens.

**CONTROLS**  
Installed fixture mounted PIR or Microwave Sensor with Daylight Priority. Remote Control or Bluetooth App Control options available.

**EMERGENCY**  
Installed 90 Minute Emergency Backup Battery Driver options available.

**LISTINGS**  
DLC Premium listed. UL certified to meet US and Canadian standards. FCC and RoHS compliant.

**WARRANTY**  
5 year exclusive limited warranty.



PIR Sensor or Bluetooth



Microwave Sensor or Bluetooth



Remote Control



LCD Remote Control




Emergency Driver




## TUNABLE CORRELATED COLOR TEMPERATURES (CCT)


3500K



4000K



5000K



## SPECIFICATIONS

### ENERGY DATA

**Input Voltage:** 120-277V  
**Input Frequency:** 50/60 Hz  
**Wattage:** 3-Wattages (75W Max, 100W Max)  
**Power Factor:** >0.9  
**Total Harmonic Distortion (THD):** <10%  
**Operating Temperature:** -4°F to 104°F (-20°C to 40°C)

### LIGHTING DATA

**Lumens:** 5200 to 13000  
**Lumens Per Watt:** 130 lm/W  
**Correlated Color Temperature (CCT):** 3-CCT (35K, 40K, 50K)  
**Dimmable:** 0-10V  
**Color Rendering Index (CRI):** >80  
**L70:** 50000 hours

## ORDERING INFORMATION

Model	Wattage	Voltage	Current	Lumens	Efficacy	CCT	Dimming	Color	Dimensions
CP01-75/60/40W-LV-3CCT	(40W 60W 75W)	120-277V	0.44A@120V, 0.16A@277V 0.66A@120V, 0.24A@277V 0.88A@120V, 0.32A@277V	5200 7800 9750	130 lm/W	(3000K, 4000K, 5000K)	0-10V	Bronze	10.06"L x 10.06"W x 2.73"H
CP01-100/80/60W-LV-3CCT	(60W 80W 100W)	120-277V	0.55A@120V, 0.24A@277V 0.73A@120V, 0.32A@277V 0.92A@120V, 0.40A@277V	7800 10400 13000	130 lm/W	(3500K, 4000K, 5000K)	0-10V	Bronze	10.06"L x 10.06"W x 2.73"H

Control	Emergency
<b>HD07VR-MH</b> 12V DC MW Bi-Level Daylight High Bay 3-Pin Smart Sensor	<b>EM8 (BLD-CM20H-1500400)</b> [INSTALLED] Emergency Backup LED Driver, 8W, 90-Min Battery
<b>HD07VR-MHB</b> 12V DC MW Bi-Level Daylight High Bay 3-Pin Smart Sensor for Haisen Blue App	
<b>HD07VR-PH</b> 12V DC PIR Bi-Level Daylight High Bay 3-Pin Smart Sensor	
<b>HD07VR-PHB</b> 12V DC PIR Bi-Level Daylight High Bay 3-Pin Smart Sensor for Haisen Blue App	
<b>HD03R</b> Sensor Remote Control (HD Series)	
<b>HD06R</b> Sensor Remote Control with LCD Display (HD Series)	

## PHYSICAL DIMENSIONS

### All Models

10.06"L x 10.06"W x 2.73"H

