

LED Semi-Cutoff Wall Pack

3-Wattages + 3-CCT (30/40/50K), Wet Rated, 130 lm/W, Dimmable + Smart

FEATURES

Lumen Output	5850 to 15600 lumens
Efficacy	130 lm/W
Input Voltage	120-277V or 277-480V
Dimmable	0-10V Continuous
CCT	Select (3000K, 4000K, 5000K)
Rating	Wet Location
Warranty	5 Years

APPLICATIONS

Premium outdoor luminaire suitable for wall mounting on building exteriors for entrances, courtyards, alleys, and pedestrian walkways.

CONSTRUCTION

Manufactured for weather-proof durability using solid heavy duty die cast aluminum housing with anti-UV polyester coating to resist water, salt, corrosion, discoloration, and scratching. Wet Location rated.

ELECTRICAL

Input voltages 120-277V or 277-480V models with 0-10V Continuous Dimming. Tunable 3-CCT (3000K, 4000K, 5000K) and Tunable 3-Wattages. Operating temperatures -4°F to 113°F (-20°C to 45°C).

MOUNTING

Wall mounted installations. Includes Liquid Level inside housing.

OPTICS

Anti-UV Prismatic Tempered Glass Lens, or Anti-UV Prismatic Polycarbonate Lens available.

CONTROLS

Installed fixture integrated Photocell sensor available. Installed fixture integrated PIR Sensor with Daylight Priority available. Remote Control available.

EMERGENCY

Installed 90 Minute Emergency Backup Battery LED Driver available.

LISTINGS

DLC Premium listed. UL certified to meet US and Canadian standards. FCC and RoHS compliant.

WARRANTY

5 year exclusive limited warranty.

80W Max and 120W Max Models



*Includes Liquid Level and Silicone Water Repellent Ring



PIR Sensor



Remote Control




Emergency Driver



TUNABLE CORRELATED COLOR TEMPERATURES (CCT)

3000K 4000K 5000K



SPECIFICATIONS

ENERGY DATA

Input Voltage: 120-277V ,277-480V

Input Frequency: 50/60 Hz

Wattage: 3-Wattages (80W Max, 120W Max)

Power Factor: >0.9

Total Harmonic Distortion (THD): <15%

Operating Temperature: -4°F to 113°F (-20°C to 45°C)

LIGHTING DATA

Lumens: 5850 to 15600

Lumens Per Watt: 130 lm/W

Correlated Color Temperature (CCT): 3-CCT (30K, 40K, 50K)

Dimmable: 0-10V

Color Rendering Index (CRI): >70

L70: 50000 hours

ORDERING INFORMATION

Model	Wattage	Voltage	Current	Lumens	Efficacy	CCT	Dimming	Color	Dimensions
FTWP-80/60/45W-LV-3CCT	45W 60W 80W	120-277V	0.41A@120V, 0.18A@277V 0.55A@120V, 0.24A@277V 0.73A@120V, 0.32A@277V	5850 7800 10400	130 lm/W	(3000K, 4000K, 5000K,)	0-10V	Bronze	14.21"L x 9.27"W x 7.31"D
FTWP-120/100/90W-LV-3CCT	90W 100W 120W	120-277V	0.83A@120V, 0.36A@277V 0.92A@120V, 0.40A@277V 1.10A@120V, 0.48A@277V	11700 13000 15600	130 lm/W	(3000K, 4000K, 5000K,)	0-10V	Bronze	14.21"L x 9.27"W x 7.31"D
FTWP-80/60/45W-HV-3CCT	45W 60W 80W	277-480V	0.18A@277V, 0.10A@480V 0.24A@277V, 0.14A@480V 0.32A@277V, 0.18A@480V	5850 7800 10400	130 lm/W	(3000K, 4000K, 5000K,)	0-10V	Bronze	14.21"L x 9.27"W x 7.31"D
FTWP-120/100/90W-HV-3CCT	90W 100W 120W	277-480V	0.36A@277V, 0.20A@480V 0.40A@277V, 0.23A@480V 0.48A@277V, 0.28A@480V	11700 13000 15600	130 lm/W	(3000K, 4000K, 5000K,)	0-10V	Bronze	14.21"L x 9.27"W x 7.31"D

Emergency

EM20 (BLD-CM20H-YYY) [INSTALLED] Emergency Backup LED Driver,
20W, 90-Min Battery

PHYSICAL DIMENSIONS

All Models

14.21"L x 9.27"W x 7.31"D

