


LED PANEL



FEATURES AND SPECIFICATIONS

Construction

- Integrative aluminum frame provides a durability structure
- Sealed housing, prevents dust and without light leak
- 5 Wattage and 5 CCT selectable switches are integrated on the driver
- Minimize Stock, 1SKU can cover Max. of 25 Models

Electrical

- Input Voltage: 120-277Vac 50/60Hz
- 0-10V dimmable, Triac dimming
- THD≤10%, PF≥0.95

Applications

- Offices, retail, schools, restaurants, healthcare, residential, and hospitality applications.

Installation

- Fixture is suitable for recessed mounting with T-bar, and accessories for suspension and surface mounting are also available. Use in ambient temperatures ranging from -20°C to 45°C

Listing

- ETL listed, suitable for damp location.
- DesignLights Consortium ®(DLC)Premium.

Warranty

- 5-year limited warranty


Specs at a Glance		* Nominal Wattage (Switchable)	
Configuration	PL01-B22-15-40W-5W5C	PL01-B24-30-72W-5W5C	PL01-B14-15-40W-5W5C
CCT (K)	3500K-4000K-5000K-5700K-6500K(Switchable)		
Wattage (W)*	15W/20W/25W/ 30W/40W Wattage Adjustable	30W/40W/50W/ 60W/72W Wattage Adjustable	15W/20W/25W/ 30W/40W Wattage Adjustable
Lumens (lm)	1,950-5,000LM	3,750-9,000LM	1,950-5000LM
Efficacy (LPW)	Up to 130	Up to 130	Up to 130
CRI	≥80		
Input Voltage	120-277VAC, 50/60Hz, 0-10V Dimmable, Triac dimming		
Operating Temp	-20°C to 45°C		
Certifications	ETL DLC 5.1 Premium		ETL
Warranty	5 Years		

Ordering information


Model	Description
PL01-B22-S40	2' x 2' Backlit Panel, Power Switchable 15W/20W/25W/30W/40W, Color Switchable 3500K/4000K/5000K/5700K/6500K, 120-277VAC
PL01-B24-S72	2' x 4' Backlit Panel, Power Switchable 30W/40W/50W/60W/72W, Color Switchable 3500K/4000K/5000K/5700K/6500K, 120-277VAC
PL01-B14-S40	1' x 4' Backlit Panel, Power Switchable 15W/20W/25W/30W/40W, Color Switchable 3500K/4000K/5000K/5700K/6500K, 120-277VAC



5-in-1 Color Temperature
5-in-1 Wattage
Hassle-Free Set up
0-10V Dimming, Triac dimming
Support Emergency, Sensor, Bluetooth



Dimensions



Accessories



Suspension mounting kits



Emergency Battery Backup



Sensor




Surface mount kit

Flexible Installation Options


Cable Mount Kit

Optional Y cable mounting kit allows for suspended installations from any ceiling type. (2 pcs/kit)





Surface Mount Kit


Optional surface mount kit allows for installation on plaster or other hard ceilings.



Wiring Diagram



Installation Instruction



Packing Information

Size/ft	L /inch	W /inch	H /inch	QTY/ctn	G.W./lbs	CTN QTY/pallet
2x2'	25.2	25.2	6.5	4	16.23	144pcs
2x4'	49.2	25.2	6.5	4	39.30	72pcs

Emergency backup installation

